


| Technical Parameters HT90W |                                     |  |                  |  |
|----------------------------|-------------------------------------|--|------------------|--|
| Engine                     |                                     | Working Range                                |                  |  |
| Engine Type<br>Power       | YUCHAI YC4FA65-T300<br>48KW/2200rpm | Max. Digging Radius<br>Max. Unloading Height | 6840mm<br>5300mm |  |
| Weight                     |                                     | Bucket                                       |                  |  |
| Overall Weight             | 7400kg                              | Bucket Capacity                              | 0.30m³           |  |

| Overall Dimension                     | HT90W |          |
|---------------------------------------|-------|----------|
| Describe                              | Unit  | Size     |
| A. Shipping Length                    | mm    | 6600     |
| B. Total Height During Transportation | mm    | 2900     |
| C. Overall Width                      | mm    | 2180     |
| D. Tail Turning Radius                | mm    | 1855     |
| E. Track Width                        | mm    | 1665     |
| F . Wheelbase                         | mm    | 2360     |
| G. Boom Length                        | mm    | 3800     |
| H. Stick Length                       | mm    | 2000     |
| . Bulldozer Size                      | mm    | 2150*400 |
| J . Bulldozer Lifting/Support Height  | mm    | 380/60   |
| K. Minimum Ground Clearance           | mm    | 220      |
| L. Ground Clearance of Counterweight  | mm    | 960      |

| Working Range and Digg          | HT90W                |                                |  |
|---------------------------------|----------------------|--------------------------------|--|
| Describe                        | Unit                 | Size                           |  |
| a . Maximum Digging Radius      | mm                   | 6840                           |  |
| b . Maximum Digging Height      | mm                   | 7540                           |  |
| c . Maximum Digging Depth       | mm                   | 3735                           |  |
| d . Maximum Unloading Height    | mm                   | 5300                           |  |
| e . Minimum Turning Radius      | mm                   | 1850                           |  |
| f . Bucket Capacity             | m³                   | 0.30                           |  |
| g . Hydraulic System Pressure   | Мра                  | 26                             |  |
| h . Hydraulic System Flow Rate  | L/min                | 140                            |  |
| i . Bucket Digging Force        | Kn                   | 45                             |  |
| j . Stick Digging Force         | Kn                   | 22                             |  |
| k . Fuel Tank Capacity          | L                    | 120                            |  |
| l . Hydraulic Oil Tank Capacity | L                    | 130                            |  |
| m. Gradient                     | %                    | ≥60                            |  |
| n . Rotation Speed              | r/min                | 12-13                          |  |
| o. Travel Speed                 | Km/h                 | 30                             |  |
| p . Braking Method              | Four Wheel Air       | Four Wheel Air Brake/Oil Brake |  |
| q . Shift Mode                  | Fully Hydraulic Auto | omatic Transmissio             |  |







### 山东帝盟重工机械有限公司 SHANDONG DIAMOND HEAVY INDUSTRY Co., Ltd

400-106-1996 Telephone: dm@sddmzg.com E-mail: International Trade: 86-534-7452888 Website: www.sddmzg.com

Shandong Dezhou (Yucheng) National High tech Development Address:







(Tiktok)

Zone Diamond Industrial Park (Website) (WeChat)





WOETH **WHEEL EXCAVATOR** 



### **Fully Hydraulic Wheeled Excavator**











The HT90W excavator is a new generation fully hydraulic wheeled excavator independently developed by DIAMOND Heavy Industries, which meets the National III emission standards and adopts a high-power and low fuel consumption standard electronic injection engine, ensuring the strong power and power reserve of the entire machine; The precise matching between the efficient hydraulic system and the bridge box ensures the arbitrary switching between working and walking states; The hydraulic system of the entire machine is matched with a load sensitive system, which has the characteristics of "coordinated action, high reliability, safety and environmental protection, comfort and convenience". At the same time, customized configurations can be provided according to customer needs, which can adapt to the needs of different countries and customers.

# Convenient Maintenance: Open Panel Design









# **Product Display**













# **Multiple Accessories To Choose From**

























# **Advantages**

### Comfortable

- A spacious and comfortable cab provides a wide and all-round view.
  A new type of suspension seat that conforms to ergonomics, thereby
- A new type of suspension seat that conforms to ergonomics, therefing improving the comfort of driver operation.

### Configure

- The National III standard electronic fuel injection engine adopts newly developed fuel saving technology, with strong power.
- The original brand's main hydraulic system is perfectly matched with the engine, providing precise flow and improving work efficiency.

#### Intelligence

 Intelligent driving computer is adopted, with big data analysis and storage function and timely warning prompt.

#### Energy

- Full time four-wheel drive, equipped with high and low gears, with high-speed walking ability, able to achieve fast transitions.
- High driving power enables the vehicle to have flexible off-road capabilities, ensuring strong off-road performance.